DULUX ACRATEX COATING SYSTEM FOR

# AAC 75MM

**BASECOAT:** RENDERWALL PLUS ACRALITE FR

**TEXTURE COATING:** COVENTRY MEDIUM

**PROTECTIVE COATING:** ACRASHIELD



## System Overview

### Application

AAC panel systems for all segments of the construction industry: new housing, alterations and additions, high & low-rise multi residential dwellings and freeway noise barriers. AAC panels are non-load bearing external wall solutions.

### Description

75mm thick panel of Autoclaved Aerated Concrete (AAC) with corrosion protected steel reinforcement embedded during production. Panels come in a variety of sizes depending on the application.

### Dulux Acratex has the performance coating soutions to deliver long term protection of facades.

When specifying your next project it makes sense to protect it against the harsh elements. That's why Dulux promotes the Acratex systems, designed to give you maximum design flexibility and maintain the coating's good looks now and for years to come.

## Dulux Acratex Coating Systems

When you specify a Dulux Acratex Coating System, you immediately get the peace of mind that comes from using a proven system from a company with the reputation of Dulux.

### Benefits of the Acratex Coating System

- Resistant to mould and dirt pick up
- Resistant to atmospheric pollution and protects from UV radiation, moisture and salt air
- Available in a wide range of Australia's most popular Dulux colours
- Easy to clean and maintain
- Weather resistant

DULUX ACRATEX COATING SYSTEM FOR

# AAC 75MM

PREPARATION




## BASECOAT

Dulux Acratex
RenderWall Plus
AcraLite FR

Acralite FR is a polymer modified and fibre reinforced cementitious skimcoat render designed for application to AAC Panels.



Trowel



Thickness

| Min DFT | Recomm DFT |
|---|---|
| 2000 microns | 4000 microns |

For more product details scan here

TEXTURE COATING



## TEXTURE COATING

Dulux Acratex Texture coating selected to desired aesthetic requirements

Example shown here:
COVENTRY MEDIUM



Trowel



Thickness

| Min WFT | Min DFT |
|---|---|
| 1076 microns | 850 microns |

For more product details scan here

PROTECTIVE COATING



## PROTECTIVE COATING

Dulux Acratex AcraShield
2 COATS

The AcraShield system is a multi-layered protective, high build elastomeric membrane coating, which protects against all climatic conditions and environmental pollutants.



Nap roller with yoke frame



Thickness

| Min WFT | Min DFT |
|---|---|
| 167 microns | 75 microns |

For more product details scan here

Colour shown: Mysterious Grove
Light Reflection Value: 58

When using dark colours, thermal stresses will increase on the coated substrate and additional control joints should be considered

Refer to DuSpec+ **AUAC01448** for full coating system specification

For further information visit **acratex.com.au** or call **13 23 77**

Disclaimer: Any advice, recommendation, information, assistance or service provided by Dulux Acratex in relation to goods manufactured by it or their use and application is given in good faith and is believed by Dulux Acratex to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Dulux Acratex is provided without liability or responsibility.

Dulux Acratex is a division of DuluxGroup (Australia) Pty Ltd. ABN 67 000 049 427. Dulux, Acratex, AcraShield, Coventry, RenderWall, AcraLite and DuSpecPlus are registered trade marks of DuluxGroup (Australia) Pty Ltd.

Dulux Acratex

0325